

EPOXY 90000

2K photoluminescent paint for floors



2 types of photoluminescent paint for professional purpose

Visibility decay: 12h
Very good glow after 10 seconds light exposition.
High resistance to abrasion, outdoors conditions, automobile traffic and skid.
Resist to temperature up to 180°C.
For professional only



POLYURETHANE PHU2K

2k photoluminescent varnish for outdoors




Store all type of electrical, natural, visible and UV lights, and glow in total obscurity for long period of time (up to 12h)

- 1 component solvanted product
- Glossy finishing, good resistance, fast drying,
- Suitable for walls indoors or outdoors
- High viscosity, Do not sag, low smell.
- Easy application over various substrates recommended with brush or roll.
- Colors: Green, Turquoise

Store all type of electrical, natural, visible and UV lights, and glow in total obscurity for long period of time (up to 12h)

Very durable paint, perfect weatherability, and resistance to chemicals

This product represents a superior quality gloss Lacquer finishing. For professional only.



EPOXY

NATURE : 2K Epoxy paint

DESTINATION : Parkings, Streets, Buidings, concrete, stone.

ASPECT: Greenish White by day, Glowing in the dark.

COLORS AND GLOW INTENSITY: Green (strong), Turquoise (good)

COVERING: 1 SQM / L - VOC: > 420 G/L - CLASS 3, GROUPE 3.3, CODE ONU: 1263, CODE IMDG: 3372

PACKAGING : 1.5L or 7.5L

MIXING : PAINT 100 PARTS, HARDENER 50 PARTS. Stir up well before use.

APPLICATION : With rolls, brushes or spraygun, recommended over white primer, with 2-4 coats.

DRYING AT 20°C : TOUCH 45 MN, AT HEART 24-48H - SHELF LIFE: STORE 6 months at 10°C / 30°C

GLOW LIFETIME: More than 20 years

POLYURETHANE

NATURE : 2K Polyurethane paint

DESTINATION : Floors, walls.

ASPECT: Greenish White by day, Glowing in the dark.

COLORS AND GLOW INTENSITY: Green (strong), Turquoise (good)

COVERING: 2.5 SQM / L - VOC: > 420 G/L - CLASS 3, GROUPE 3.3, CODE ONU: 1263, CODE IMDG: 3372

PACKAGING : 1.33L or 4L

MIXING : PAINT 100 PARTS, HARDENER 30 PARTS. Stir up well before use.

APPLICATION : With rolls, brushes or spraygun, recommended over white primer, with 2-4 coats.

DRYING AT 20°C : TOUCH 45 MN, AT HEART 24-48H - SHELF LIFE: STORE 6 months at 10°C / 30°C

GLOW LIFETIME: More than 20 years

Luminance (mcd/m²)

Colors	1MIN	10MIN	60MIN	Lum
GREEN	3800	685	91	12350
TURQUOISE	1800	427	71	9230

Tests done with a 100µm coat, done with 4 passes. Mentionned datas has been made in accordance with DIN67510 Part I. Luminance in microcandelas/m²

View our full line of products at www.stardustcolors.co.uk